

>> 钢丝绳质量证明书<< Wire Rope Quality Certificate

编号:QER-QA-003-08

Gustav Wolf Wire Rope (Suzhou) Co., Ltd.
Tel:+86(512) 66939388
Fax:+86(512) 66939188
E-mail:info@gustav-wolf.com.cn

Manufacture license: (苏) XK05-005-00020

检验标准	Inspection certificate
EN10204 / ISO4344	EN10204 / ISO4344

客户	苏州威庭机电科技有限公司		
Company			
订单号	VTSP25307		
Order			
质量证明书编号	2025061810		
Quality certificate No			
产品型号	721213032		
Article No.			
公称直径	13		mm
Nominal diameter			
实际直径	13.10		mm
Actual diameter			
长度	1700*2		m
Length			
净重	2414.0		kg
Net weight			
结构	PAWO F10		
Construction			
捻法	Regular Lay right lay		
Type and direction of lay			
抗拉强度	1570		N/mm²
Tensile grade			
表面	Bright		
Finish			
最小破断拉力	113.4		kN
Min. breaking load			
实际破断拉力	120.52		kN
Actual breaking load			
出厂编号	616309.05/06		
GWC—reel—No.			
交货日期	2025/6/18		
Delivery date			
钢丝绳中钢丝的试验结果	ok		
Individual wire test			

钢丝 wire	公称直径 1) nominal diameter	实际直径 actual diameter	最小破断力 breaking load	抗拉强度 2) tensile strength	弯折次数 3) bending	扭转次数 4) torsion
	(mm)	(mm)	(N)	(N/mm ²)		
9*1	0.54			1960		
9*5	0.68	0.680	649	1570	17	38
9*5	0.32	0.320		1960		
9*10	0.71	0.710	685	1570	19	38
检验项目 Inspection item	结果 Result					
钢丝绳外观 Appearance	pass					
松散 Loose	pass					

日期: 2025/6/16
Date

检验者: Li Baobao
Checked by
QC01 Passed

产品执行ISO 3178标准。It is certified that this rope conforms to ISO 3178.

产品符合 BS 302 标准 1 ~ 4部分。It is certified that this rope fulfills the BS 302 part 1 ~ 4.

产品参照 DIN EN 12385 and DIN EN 10264技术标准。This rope delivery corresponds to the technical terms of delivery to- DIN EN 12385 and DIN EN 10264

1) 专业的德国生产技术。Specified by the manufacturer.

2) 抗拉强度检测执行ISO 6892标准。Tensile test according to ISO 6892.

3) 反向弯曲测试执行ISO 7801标准。Reverse Bend test according to ISO 7801 4) 扭转测试执行ISO 7800标准。Torsion test according to ISO 7800.

5) 松散执行GB8903标准。

6) 钢丝绳外观执行GB/T 8706-2006标准。