

Gustav Wolf Wire Rope (Suzhou) Co., Ltd.
Tel: +86(512) 66939388
Fax: +86(512) 66939188
E-mail: info@gustav-wolf.com.cn

>> 钢丝绳质量证明书 <<
Wire Rope Quality Certificate

编号: QER-QA-003-08

Manufacture license: (苏) XK05-005-00020

检验标准	Inspection certificate
EN10204 / ISO4344	EN10204 / ISO4344

客户	苏州威庭机电科技有限公司		
Company			
订单号	VTSP25307		
Order			
质量证明书编号	2025061808		
Quality certificate No			
产品型号	721208032		
Article No.			
公称直径	8		mm
Nominal diameter			
实际直径	8.17		mm
Actual diameter			
长度	4000		m
Length			
净重	1080.0		kg
Net weight			
结构	PAWO F10		
Construction			
捻法	Regular Lay right lay		
Type and direction of lay			
抗拉强度	1570		N/mm²
Tensile grade			
表面	Bright		
Finish			
最小破断拉力	43.2		kN
Min. breaking load			
实际破断拉力	44.95		kN
Actual breaking load			
出厂编号	516531.02		
GWC—reel—No.			
交货日期	2025/6/18		
Delivery date			
钢丝绳中钢丝的试验结果	ok		
Individual wire test			

钢丝绳	公称直径 1)	实际直径	最小破断力	抗拉强度 2)	弯折次数 3)	扭转次数 4)
wire	nominal diameter	actual diameter	breaking load	tensile strength	bending	torsion
	(mm)	(mm)	(N)	(N/mm ²)		
9*1	0.22			1960		
9*4	0.42	0.420	241	1570		
9*4	0.22	0.220		1960		
9*8	0.51	0.510	336	1570	16	39
检验项目	结果					
Inspection item	Result					
钢丝绳外观	pass					
Appearance						
松散	pass					
Loose						

日期: 2025/6/16
Date

检验者: Li baobao
Checked by
QC01 Passed

产品执行ISO 3178标准。It is certified that this rope conforms to ISO 3178.
产品符合 BS 302 标准 1 ~ 4 部分。It is certified that this rope fulfills the BS 302 part 1 ~ 4.
产品参照 DIN EN 12385 and DIN EN 10264 技术标准。This rope delivery corresponds to the technical terms of delivery to DIN EN 12385 and DIN EN 10264
1) 专业的德国生产技术。Specified by the manufacturer. 2) 抗拉强度检测执行ISO 6892标准。Tensile test according to ISO 6892.
3) 反向弯曲测试执行ISO 7801标准。Reverse Bend test according to ISO 7801. 4) 扭转测试执行ISO 7800标准。Torsion test according to ISO 7800.
5) 松散执行GB8903标准。 6) 钢丝绳外观执行GB/T 8706-2006标准。