

Gustav Wolf Wire Rope (Suzhou) Co., Ltd.
Tel: +86(512) 66939388
Fax: +86(512) 66939188
E-mail: info@gustav-wolf.com.cn

>> 钢丝绳质量证明书 <<
Wire Rope Quality Certificate
Manufacture license: (苏) XK05-005-00020

编号: QER-QA-003-08

检验标准 EN10204 / ISO4344	Inspection certificate EN10204 / ISO4344
---------------------------	---

客户 Company	苏州威庭机电科技有限公司		
订单号 Order	VTSP25307		
质量证明书编号 Quality certificate No	2025061807		
产品型号 Article No.	721210032		
公称直径 Nominal diameter	10		mm
实际直径 Actual diameter	10.14		mm
长度 Length	3000*4		m
净重 Net weight	5040.0		kg
结构 Construction	PAWO F10		
捻法 Type and direction of lay	Regular Lay right lay		
抗拉强度 Tensile grade	1570		N/mm²
表面 Finish	Bright		
最小破断拉力 Min. breaking load	67.2		kN
实际破断拉力 Actual breaking load	72.84		kN
出厂编号 GWC—reel—No.	516559.01/02/03/516324.06		
交货日期 Delivery date	2025/6/18		
钢丝绳中钢丝的试验结果 Individual wire test	ok		

钢丝绳 wire	公称直径 1) nominal diameter	实际直径 actual diameter	最小破断力 breaking load	抗拉强度 2) tensile strength	弯折次数 3) bending	扭转次数 4) torsion
	(mm)	(mm)	(N)	(N/mm²)		
9*1	0.27			1960		
9*4	0.52	0.520	360	1570	17	38
9*4	0.27	0.270		1960		
9*8	0.64	0.640	580	1570	13	42
检验项目 Inspection item	结果 Result					
钢丝绳外观 Appearance	pass					
松散 Loose	pass					

日期: 2025/6/16
Date

检验者: Li Baobao
Checked by
QC01 Passed

产品执行ISO 3178标准。It is certified that this rope conforms to ISO 3178.

产品符合 BS 302 标准 1 ~ 4 部分。It is certified that this rope fulfills the BS 302 part 1 ~ 4.

产品参照 DIN EN 12385 and DIN EN 10264 技术标准。This rope delivery corresponds to the technical terms of delivery to- DIN EN 12385 and DIN EN 10264

1) 专业的德国生产技术。Specified by the manufacturer.

2) 抗拉强度检测执行ISO 6892标准。Tensile test according to ISO 6892.

3) 反向弯曲测试执行ISO 7801标准。Reverse Bend test according to ISO 7801.

4) 扭转测试执行ISO 7800标准。Torsion test according to ISO 7800.

5) 松散执行GB8903标准。

6) 钢丝绳外观执行GB/T 8706-2006标准。